

# HG 2620 E

## NEW!

Available October 2016

### Technical Specifications

**Voltage:** 120 VAC / 60Hz  
**Output:** 1750 watts  
**Amps:** 14.6  
**Temperature:** 120 – 1300 °F (50 – 700 °C) (continuously variable)  
**Airflow rate:** 2 – 13 cfm. (continuously variable)  
**Air pressure:** 3,000 Pa  
**Highlights:** Restart protection, LCD display always in view, 4 settings programmable, locable override funktion (LOC), single-hand operation by toggle, magnesium guard sleeve, plug-in heating element, residual heat indicator, fine dust filter, construction use, easily replaceable power cord, ergonomic soft grip handle, optional temperature scanner

**Power cord:** Industrial grade rubber  
**Motor:** Brushless motor  
**Heating element:** Ceramic heating element  
**Motor lifetime:** Approx. 10,000 hrs.  
**Heater lifetime:** Approx. 800 hrs.  
**Accessories:** Use of our professional accessories

**Dimensions:** 14.10" x 3.60" x 3.70" (l x w x h)  
**Net Weight:** 1.85 lbs (29.63oz)  
**Single Sell Pack Box :** Dimensions: 17.13" x 4.13" x 4.13"  
 Weight: 3.26 lbs (52.10 oz)

**Single Sell Pack Case:** Dimensions: 15.35" x 4.33" x 12.6"  
 Weight: 5.17 lbs (82.65 oz)

**Country of origin:** Romania  
**Warranty:** One year limited



UPC-Code	Prod. No.	Version
018139376002	110025600	Box
018139376019	110047485	Case



RoHS  
Compliant



double insulated

ISO  
9001:  
2015  
14001:  
2015

# HG 2220 E

**NEW!**


Available October 2016

## Technical Specifications

Voltage:	120 VAC / 60Hz
Output:	1500 watts
Amps:	12.5
Temperature:	120 – 1100 °F (50 - 600°C) thumbweel setting
Airflow rate:	4-7 / 6-12 cfm.
Stages:	2
Highlights:	Continuously variable temperature, fine dust filter, ergonomic soft grip handle, easily replaceable power cord
Power cord:	Industrial grade rubber
Motor:	Brush motor
Heating element:	Ceramic heating element
Motor lifetime:	750h
Accessories:	Use of our professional accessories
Dimensions:	13.30" x 3.00" x 3.50" (l x w x h)
Net Weight:	1.34 lbs (21.51 oz)
Single Sell Pack:	Dimensions: 17.13" x 4.13" x 4.13" Weight: 2.59 lbs (41.48 oz)
Country of origin:	Romania
Warranty:	One year limited



UPC-Code	Prod. No.
018139376200	110025601



# HG 2520 E

**NEW!**


Available October 2016

## Technical Specifications

Voltage:	120 VAC / 60Hz
Output:	1750 watts
Amps:	14.6
Temperature:	120 – 1300 °F (50 – 700 °C) (continuously variable)
Airflow rate:	2 – 13 cfm. (continuously variable)
Air pressure:	3,000 Pa
Highlights:	Restart protection, LCD display, 4 settings programmable, locable override funktion (LOC), single-hand operation by toggle, magnesium guard sleeve, plug-in heating element, residual heat indicator, construction use, easily replaceable power cord, ergonomic soft grip handle, optional temperature scanner
Power cord:	Industrial grade rubber
Motor:	Brushless motor
Heating element:	Ceramic heating element
Motor lifetime:	Approx. 10,000 hrs.
Heater lifetime:	Approx. 800 hrs.
Accessories:	Use of our professional accessories
Dimensions:	11.20" x 3.80" x 8.20" (l x w x h)
Net Weight:	1.85 lbs (29.63 oz)
Single Sell Pack:	Dimensions: 15.35" x 4.33" x 12.6" Weight: 5.15 lbs (82.44 oz)
Country of origin:	Romania
Warranty:	One year limited



UPC-Code	Prod. No.
018139375906	110025599



# HG 2320 E

**NEW!**


Available October 2016

## Technical Specifications

Voltage:	120 VAC / 60Hz
Output:	1600 watts
Amps:	13.3
Temperature:	120 – 1200 °F (50 – 650 °C)
Airflow rate:	4 – 13 cfm. (continuously variable)
Stages:	2 (continuously variable)
Highlights:	Higher durability (+20 %), optimized weight balance, LCD-Display, 4 settings programmable, heat build-up warning, hanging ring, easily replaceable power cord, residual heat indicator, optional temperature scanner and fine dust filter
Power cord:	Industrial grade rubber, length: 6ft
Motor:	Brush motor
Heating element:	Ceramic heating element
Motor lifetime:	1000h
Accessories:	Use of our standard accessories
Dimensions:	9.96" x 3.41" x 7.87" (l x w x h)
Net Weight:	2.19 lbs (35.1 oz)
Single Sell Pack:	Dimensions: 10.20" x 3.54" x 9.33" Weight: 2.60 lbs (41.66 oz)
Country of origin:	Romania
Warranty:	One year limited



UPC-Code	Prod. No.
018139375708	110025598



# HL 2020 E

**NEW!**

Available October 2016

## Technical Specifications

Voltage:	120 VAC / 60Hz
Output:	1600 watts
Amps:	13.3
Temperature:	120 – 1150 °F (50 – 620 °C)
Airflow rate:	4 / 4-8 / 6-13 cfm.
Stages:	3
Highlights:	Higher durability (+20 %), optimized weight balance, LCD-Display, heat build-up warning, hanging ring, easily replaceable power cord, residual heat indicator, optional temperature scanner and fine dust filter
Power cord:	Industrial grade rubber, length: 6ft
Motor:	Brush motor
Heating element:	Ceramic heating element
Motor lifetime:	600h
Accessories:	Use of our standard accessories
Dimensions:	9.96" x 3.37" x 7.87" (l x w x h)
Net Weight:	2.19 lbs (35.10 oz)
Single Sell Pack:	Dimensions: 10.20" x 3.54" x 9.33" Weight: 2.60 lbs (41.66 oz)
Country of origin:	Romania
Warranty:	One year limited



UPC-Code	Prod. No.
018139375500	110025597



RoHS  
Compliant



double insulated

**ISO**  
9001:  
2015  
14001:  
2015

# HL 1920 E

**NEW!**

Available October 2016

## Technical Specifications


Voltage:	120 VAC / 60Hz
Output:	1500 watts
Amps:	12.5
Temperature:	120 – 1100 °F (50 – 600 °C)
Airflow rate:	4 / 4-8 / 6-13 cfm.
Stages:	3
Highlights:	Higher durability (+20 %), optimized weight balance, hanging ring, optional temperature scanner and fine dust filter
Power cord:	Industrial grade rubber, length: 6ft
Motor:	Brush motor
Heating element:	Ceramic heating element
Motor lifetime:	600h
Accessories:	Use of our standard accessories
Dimensions:	9.96" x 3.33" x 7.87" (l x w x h)
Net Weight:	1.9 lbs (30.37 oz)
Single Sell Pack:	Dimensions: 10.20" x 3.54" x 9.33" Weight: 2.31 lbs (36.93 oz)
Country of origin:	Romania
Warranty:	One year limited



UPC-Code	Prod. No.
----------	-----------

018139375302

110025596



RoHS  
Compliant



double insulated

**ISO**  
9001:  
2015  
14001:  
2015

# HL 1820 S

**NEW!**

Available October 2016

## Technical Specifications

Voltage:	120 VAC / 60Hz
Output:	1400 watts
Amps:	11.7
Temperature:	120 / 750 / 1100 °F (50 / 400 / 600 °C)
Airflow rate:	4 / 7 / 13 cfm.
Stages:	3
Highlights:	Higher durability (+20 %) optimized weight balance
Power cord:	Industrial grade rubber, length: 6ft
Motor:	Brush motor
Heating element:	Ceramic heating element
Motor lifetime:	600h
Accessories:	Use of our standard accessories
Dimensions:	9.96" x 3.33" x 7.87" (l x w x h)
Net Weight:	1.77 lbs (28.36 oz)
Single Sell Pack:	Dimensions: 10.20" x 3.54" x 9.33" Weight: 2.18 lbs (34.92 oz)
Country of origin:	Romania
Warranty:	One year limited




UPC-Code

018139375203

Prod. No.

110025541



RoHS  
Compliant



double insulated

**ISO**  
9001:  
2015  
14001:  
2015

# HL 1620 S

**NEW!**


Available October 2016

## Technical Specifications

Voltage:	120 VAC / 60Hz
Output:	1300 watts
Amps:	10.8
Temperature:	575 / 950 °F (300 / 500 °C)
Airflow rate:	8 / 13 cfm.
Stages:	2
Highlights:	Higher durability (+20 %), optimized weight balance
Power cord:	Industrial grade rubber, length: 6ft
Motor:	Brush motor
Heating element:	Micanite heating element
Motor lifetime:	600h
Accessories:	Use of our standard accessories
Dimensions:	9.92" x 3.37" x 7.87" (l x w x h)
Net Weight:	1.65 lbs (26.4 oz)
Single Sell Pack:	Dimensions: 10.20" x 3.54" x 9.3" Weight: 2.06 lbs (32.98 oz)
Country of origin:	Romania
Warranty:	One year limited



UPC-Code	Prod. No.
018139375104	110023455



RoHS  
Compliant



double insulated

**ISO**  
9001:  
2015  
14001:  
2015