

## TEMPOFLUX 2 direct flush valve

Ref. 762901

Time flow valve for direct flush 6L single flush



### DESCRIPTION

#### TEMPOFLUX 2 direct flush valve - Ref. 762901

Recessed time flow valve for direct flush:  
 Multipurpose recessing housing.  
 Chrome-plated metal wall plate Ø 195mm.  
 Recessing depth can be adjusted from 0 - 20mm.  
 6L single flush.  
 Soft-touch operation.  
 Vacuum breaker.  
 Integrated stopcock and flow rate / flush volume adjuster.  
 Solid brass body.  
 Chrome-plated metal push-button.  
 In-line inlet M3/4".  
 Outlet connection for PVC tube Ø 26/32mm.  
 Acoustic level complies with European standard EN 12541 class II.

This model does not have a waterproof recessing housing. The installer must ensure that the recessing area is waterproof and any leaks or condensation can drain away (see installation guide).  
 10-year warranty.

### TECHNICAL FEATURES

#### TEMPOFLUX 2 direct flush valve - Ref. 762901

Connector	3/4"
Technology	Time flow
Flow rate	6l
Standards and certifications	 
Warranty	

### ADVANTAGES

-  Soft-touch operation
-  Direct flush: no stagnant water
-  Wall recessed installation
-  Powerful flush and available immediately

