

Cim RED6/1

FULL BORE BALL VALVE - RED 5 SERIES - ALUMINIUM BUTTERFLY HANDLE



This article was made in compliance with the quality management requirements of ISO 9001 standard. All articles are tested according to the EN 12266-1 standard.

It can be used in a wide variety of sectors: heating, air conditioning, water, sanitary systems, pneumatic systems, oil pipelines, gasoline networks, saturated steam and generally with any non corrosive liquid.

It is guaranteed for 5 years.


It is made of a brass alloy that complies with standard EN 12165-CW617N-DW.

Nominal Pressure:

PN 50 (1/2"); PN 40 (3/4" ÷ 1"); PN 30 (1"1/4 ÷ 1"1/2); PN 25 (2")

Operating temperature: -20 ÷ 150°C

FLOW AND PRESSURE DROP



Notes:


Giacomo Cimberio S.p.A. - rev: 9/2019-06-17

Cim RED6/1 - © Cav. Uff.

1 l/min = 0.06 m3/h1 m3/h = 16,67 l/min1 bar = 10.000 mm w.c.

1 psi = 690 mm w.c.

PRESSURE TEMPERATURE RATINGS



Notes:

1 bar = 14,5 psi


1 bar = 14,5 lbf/in2

 $^{\circ}C = 5/9 \times (^{\circ}F-32)$

 $^{\circ}F = 32 + (9/5 \times ^{\circ}C)$



TECHNICAL DRAWING



DN	1/2"	3/4"	1''	1''1/4	1''1/2	2"			
Ø mm	14	19	24	29	37	47			
Grms.	145	235	350	475	815	1240			
Α	55	55	75	75	105	105			
В	39	43,5	48	53	68	74			
С	47	53,5	66	74	88	102			
D	12	12	15	16	18	19			
CH	25	31	37	47	54	66			

Thread: ISO 228

Upon request: ANSI B.1.20.1 - NPT

TECHNICAL CHARACTERISTICS

KV CM CS MT									
DN	1/2"	3/4"	1"	1"1/4	1"1/2	2"			
Ø mm	14	19	24	29	37	47			
KV	15	37	63	108	179	256			
СМ	1	1,5	2,5	3	8	11			
CS	2,5	5	6	10	18	20			
MT	24	24	26	26	88	88			

KV = Capacity in m³/h at pressure drop of 1 bar.

CM = Operating torque in Nm.

CS = Starting torque in Nm.

MT = Stem breaking torque in Nm.

REACH Regulation

According to article 33 of REACH Regulation, we inform you that the components made of bronze and brass alloys that are parts of the articles we supply, contain the lead (as alloy component) in a higher quantity of the limit of 0,1% in weight. Lead has been inserted in the list of SVHC substances nominated for the authorisation process, in the updating published by the European Chemical Agency ECHA on 27th June 2018. Lead has been introduced with the following information:

Substance: LeadCAS: 7439-92-1EC: 231-100-4

List: SVHC

Data of Inclusion: 27th June 2018

Since lead is an element of the alloy, no exposure is expected and consequently, no further information is requested for the safe use of this product.

The list is available at the following link: https://echa.europa.eu/it/candidate-list-tableand since it is a continuously updated list, we declare the constant monitoring about insertion of new substances and the prompt on time

information to our customers in case such substances should be contained in the products we supply.

Make sure product materials and features are suitable for system scope and conform to the local regulations in force

OUR CERTIFICATIONS











